

DPS PUMPS

SELF-PRIMING TRASH & SEWAGE PUMP

TS – TSH Series 2" to 12"



**Heavy Duty
Industrial**



These pumps are designed to handle mild industrial corrosives, mud and slurries containing SOLIDS

DPS PUMPS

A Division of Diesel Parts & Service Pty Ltd A.C.N 009 818 848

21 Hilda Street

Hamilton, Brisbane, Qld. 4007

Phone: (07) 32681062

Fax: (07) 38681330

www.dieselparts.com.au

DPS PUMPS

SELF-PRIMING TRASH & SEWAGE PUMP



SPECIFICATIONS:

- External Shimless Adjustment System
- Solids Handling Impeller – up to 3" (76.2mm)
- Oil Lubricated Mechanical Cartridge Seal
- Removable Coverplate
- Removable BPO Pedestal Assembly
- Oil Lubricated Bearings

Model	Maximum Volume	Maximum Head	Maximum Suction	Maximum Speed	Maximum Power	Maximum Solids	Inlet & Outlet
TS-050	13 l/s	36 m	7.6 m	2900rpm	7.5 kW	1.3/4"	2" X 2"
TS-080	30 l/s	35 m	7.6 m	2150rpm	15 kW	2.1/2"	3" X 3"
TS-100	45 l/s	35 m	7.6 m	1950rpm	23 kW	3"	4" X 4"
TS-150	92 l/s	33 m	7.6 m	1550rpm	30 kW	3"	6" X 6"
TS-200	167 l/s	34 m	7.0 m	1350rpm	50 kW	3"	8" X 8"
TS-250	215 l/s	39 m	6.7 m	1450rpm	85 kW	3"	10" X 10"
TS-300	360 l/s	43 m	4.9 m	1250rpm	90 kW	3"	12" X 12"

High Head Models

TS-080H	24 l/s	62 m	7.6 m	2150rpm	20 kW	13/16"	3" X 3"
TS-100H	41 l/s	59 m	5.2 m	2150rpm	32 kW	1.1/8"	4" X 4"
TS-150H	86 l/s	58 m	4.5 m	1950rpm	55 kW	1.1/4"	6" X 6"

Standard Pump:

Cast iron body, Ductile iron impeller, High tensile steel shaft, double floating, self aligning, oil bath lubricated mechanical cartridge seal.



Distributed By:
Diesel Parts and Service
21 Hilda Street
Hamilton, Brisbane, QLD
4007
Ph: (07)32681062
Fax: (07) 38681330